





EI30 FD30 EITHER SIDE



3c Stability*



Door Leaf

- Huet multi-layer insulating core
- Thickness: 51mm hardwood stiles all round
- High stability leaf due to the inclusion of 2 steel sheets
- Plywood panels for exterior use

Door Frame

- Hardwood (of our choice)
- Rebated monoblock frame
- Variety of widths
- Extension linings available
- Frame can be lacquered, stained or varnished
- Frame can be wrapped with wood veneer to match door leaf facings

Perimeter Seals

Ironmongery

and handles

4 hinges

Spy hole

 Combined smoke and acoustic seals fitted within the frame and leaf

Cut-outs/mortices are available

 Cut-outs/mortices are available to suit a large choice

to suit a variety of locks

of electromagnetic lock

 Swiss threshold 35x20mm wrapped with stainless steel

Choice of Door Facings

- Rough to be finished
- Primed
- Wood veneers to match approved samples
- Laminated
- Engraved to a wide choice of standard and bespoke finishes

*Stability of the door leaf is an important factor, particularly in areas of temperature variance between rooms or between rooms and corridors. Any distortion of the door leaf will result in the seals not functioning correctly. With the inclusion of a minimum of 2 steel sheets and other materials, Huet door leafs offer less than 2mm of distortion. The result is a door leaf and seal which continues to perform even with wide temperature differences.



Tel: +33 22 812 0413

















